



JAGUAR XK120 (FA2045/2678 Filter head) Eng. No. W1001 - W4382 OIL FILTER ADAPTOR FITTING INSTRUCTIONS

Please read all the instructions before starting work on your car.

The kit contains:

- 1 x large rubber o-ring
- Long bolt
- 1 x small rubber o-ring
- Aluminium adaptor plate
- Fibre washer
- Filter Bolt
- Oil filter



This adaptor is intended for the early XK120 engine which is fitted with a Tecalemit FA2045 filter head.

As it is common to find the filter head from one Jaguar engine fitted to another please check that you have the correct adaptor for your engine. If in doubt contact your supplier.

Remove the bowl and the original filter. Remove the old seal for the filter bowl which will be embedded in a groove in the filter head; make sure that the groove is clean and contains no remains of the old seal or gasket sealant. Remove the snap-ring, and the splash plate (this looks like a large steel washer) in the centre of the filter head. If there is a felt washer under the plate remove this also.

Fit the larger of the two o-rings supplied in the outer groove of the filter head making sure that it is seated correctly. Place the long bolt through the fibre washer and insert the bolt through the top of the filter head. Fit the smaller o-ring over the boss in the filter head (where the splash plate was fitted). Place the large alloy adaptor plate in position in the head and connect with the long bolt. Screw the two together tightly, but do not overtighten (Loctite is recommended here).

You are now ready to fit a spin-on filter to your Jaguar. We recommend a Crosland 357, Fram 2857A or similar high quality filter. Fill the filter with oil before fitting and grease the filter's rubber sealing ring. Always check for oil leaks when starting the engine after replacing the filter. Renew the filter at the recommended intervals.



Large o-ring here

Small o-ring here

Also available for your Jaguar: braided stainless steel flexible brake and clutch hoses, fuel and oil lines, fuel filters and pumps, oil coolers etc. Ask for details.

Flexolite, Unit 7 Merebrook Business park, Malvern, Worcs, WR13 6NP
Tel: 01684 368539 E-mail: sales@flexolite.co.uk